



**FITAS LED**  
CASATREND

## Flash SDM 3528-300 – IP 20 – 4,8 W/M

**GTV**



Rolo de 5 metros.

L (mm)	Corte (cm)	IP	W/m	V	lm/m	LEDs/m	Luz	Código
8	5	20	4,8	12	300	60	3200 K	LD.3528.300.20.CB
8	5	20	4,8	12	300	60	4000 K	LD.3528.300.20.NE4P
8	5	20	4,8	12	300	60	6500 K	LD.3528.300.20.ZB



## Flash SDM 3528-600 – IP 20 – 9,6 W/M

**GTV**

Rolo de 5 metros.


L (mm)	Corte (cm)	IP	W/m	V	lm/m	LEDs/m	Luz	Código
8	2,5	20	9,6	12	550	120	3200 K	LD.3528.600.20.CB
8	2,5	20	9,6	12	550	120	6500 K	LD.3528.600.20.ZB



## Flash SDM 2835-300 – IP 20 – 6 W/M

**GTV**

Rolo de 5 metros.



L (mm)	Corte (cm)	IP	W/m	V	lm/m	LEDs/m	Luz	Código
8	5	20	6	12	750	60	3200 K	LD.2835.300.20.CB
8	5	20	6	12	750	60	4000 K	LD.2835.300.20.NE4P
8	5	20	6	12	750	60	6500 K	LD.2835.300.20.ZB



## Flash SDM 3528-600 – IP 20 – 9.6 W/M – 50 m

**GTV**

Rolo de 50 metros.

L (mm)	Corte (cm)	IP	W/m	V	lm/m	LEDs/m	Luz	Código
8	5	20	9,6	12	550	120	3200 K	LD.3528.600.20.CB.50
8	5	20	9,6	12	550	120	4000 K	LD.3528.600.20.NE4.50
8	5	20	9,6	12	550	120	6500 K	LD.3528.600.20.ZB.50



## Flash SDM 2835-300 – IP 65 – 6 W/M

**GTV**

Rolo de 5 metros.

L (mm)	Corte (cm)	IP	W/m	V	lm/m	LEDs/m	Luz	Código
8	5	65	6	12	700	60	3200 K	LD.2835.300.65.CB
8	5	65	6	12	700	60	6500 K	LD.2835.300.65.ZB



## Flash SDM 2835-600 – IP 20 – 10,8 W/M

Rolo de 5 metros.

L (mm)	Corte (cm)	IP	W/m	V	lm/m	LEDs/m	Luz	Código
8	5	20	10,8	12	1000	60	2700 K	LT.2835.600.2700K
8	5	20	10,8	12	1000	60	3000 K	LT.2835.600.3000K
8	5	20	10,8	12	1100	60	4000 K	LT.2835.600.4000K
8	5	20	10,8	12	1200	60	6000 K	LT.2835.600.6000K



## Flash SDM 2835-600 – IP 20

**GTV**

Rolo de 5 metros.

Potência variável com o comprimento da fita:

L (m)	1	2	3	4	5
W	10	18	25	30	33

L (mm)	Corte (cm)	IP	W/m	V	lm/m	LEDs/m	Luz	Código
5	2,5	20	6,6	12	750	120	3200 K	LD.2835.600.5MM.20.CB
5	2,5	20	6,6	12	750	120	4000 K	LD.2835.600.5MM.20.NE4
5	2,5	20	6,6	12	750	120	6500 K	LD.2835.600.5MM.20.ZB



## Flash SDM 2835-600 – IP 20

**GTV**

Rolo de 5 metros.

Potência variável com o comprimento:

L (m)	1	2	3	4	5
W	19	36	48	57	60

L (mm)	Corte (cm)	IP	W/m	V	lm/m	LEDs/m	Luz	Código
10	2,5	20	12	12	1600	120	3200 K	LD.2835.600.20.CB
10	2,5	20	12	12	1600	120	4000 K	LD.2835.600.20.NE4
10	2,5	20	12	12	1600	120	6500 K	LD.2835.600.20.ZB



## Flash SDM 2835-300 – IP 20 – 6 W/M – 50 m

Rolo de 50 metros.

**GTV**

L (mm)	Corte (cm)	IP	W/m	V	lm/m	LEDs/m	Luz	Código
8	5	20	6	12	750	60	3200 K	LD.2835.300.20.CB.50
8	5	20	6	12	750	60	4000 K	LD.2835.300.20.NE4P.50
8	5	20	6	12	750	60	6500 K	LD.2835.300.20.ZB.50



## RGB 30 ZLD e ZLF – IP 20/45 – 6 W/M – 5 m

Rolo de 5 metros.

**DesignLight**

L (mm)	Corte (cm)	IP	W/m	V	lm/m	LEDs/m	Luz	Código
10	10	20	6	12	–	–	RGB	ZLD.RGB.5M.01W
10	10	45	6	12	–	–	RGB	ZLF.RGB.5M.01W



## LED Cob – IP 20 – 10 W/M – 5 m

**GTV**

Rolo de 5 metros.



L (mm)	Corte (cm)	IP	W/m	V	lm/m	LEDs/m	Luz	Código
8	2,5	20	10	12	750	480	2700 K	LD.COB.12V.CBPQ
8	2,5	20	10	12	800	480	4000 K	LD.COB.12V.NEPQ
8	2,5	20	10	12	800	480	6500 K	LD.COB.12V.ZBPQ

### União para Fita Cob



LD.ZT8.COB

### União de Canto 90° para Fita Cob



LD.ZTKT8.COB



### Cabo de Ligação Rápida para Fita Cob


LD.ZT82MAMP.COB

## Neon Flex – IP 65 – 9,6/11 W/M – 5/50 m



Com possibilidade de comprar rolo de 5 metros ou de 50 metros (com W/m diferentes).

C (m)	L (mm)	Corte (cm)	IP	W/m	V	lm/m	LEDs/m	Luz	Código
5	6 x 12	1	65	máx. 11	12	1180-1240	100	3000 K	N.6X12.Z.11W.30K.01
5	6 x 12	1	65	máx. 11	12	1180-1240	100	4000 K	N.6X12.Z.11W.40K.01
5	6 x 12	1	65	máx. 11	12	1180-1240	100	6500 K	N.6X12.Z.11W.60K.01
50	6 x 12	2,5	65	9.6	12	1180-1240	100	3200 K	FN12V09630K
50	6 x 12	2,5	65	9.6	12	1180-1240	100	4200 K	FN12V09642K
50	6 x 12	2,5	65	9.6	12	1180-1240	100	6000 K	FN12V09660K



### Terminal



N-ZASL-6X12-01

### Fixador



N-UCH-6X12-01